



SAFETY INTERLOCK SYSTEM.
INTERGRATED SPOTLIGHT
DUAL GAS FIRES OR SINGLE W/WOOD FIRE

OVEN WEIGHT: approx. X2
TOP SECTION = 1450kg
LOWER SECTION = 900kg

SERVICES LEGEND.		<p>Hatched area indicates insulation(50mm) and required air gap (25mm) Total 75mm.</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PHOENIX OVENS PTY.LTD.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PHOENIX OVENS PTY.LTD. IS PROHIBITED.</p> <p>PHOENIX OVENS. AUSTRALIA.</p> <p>TITLE: FLAMETREE FT1875.CUST</p> <p>DWG NO. 2XFT1700875</p> <p>SCALE 1:20 DO NOT SCALE DRAWING SHEET 1 OF 1</p>
SYMBOL	SERVICE	
	220/240V Single phase 2 X 10amp Wall socket.	
	Gas connection: 2X 70mJ/oven Total 280mJ. (Nat.)	
	EXHAUST CONNECTION: 300x300mm Universal flange 1000l/sec. @150Pa./oven 2000l/sec. TOTAL	

